

### FLAME RETARDANT PREMIUM HARD SURFACE PROTECTION FILM



Product Code	Pricing Unit	Colour	Dimensions	Thickness	Pack Quantity	Pallet Quantity
PFMF11E	EACH	Blue	600mm x 100m	65 microns	9	90

#### Product Description:

Proguard Flame Retardant Premium Hard Surface Protection Film is perfect for protecting hard surfaces from spillages and debris during building, painting, DIY projects, house moves, parties and other events to help reduce clean up time. The adhesive backing adheres to most hard surfaces and ensures that the film stays securely in place, making it safer to use than traditional dust sheets and polythene. After use, it can be peeled away without leaving any residue.

The rolls are forward wound meaning the adhesive side is on the inside which makes the rolls perfect for application with our Proguard Film Applicator or by hand. As the adhesive is on the inside it is not exposed to dirt.

This hard surface film has the added benefit of being flame retardant and anti-slip due to its embossed finish.

#### Benefits:

- Self-adhesive for easy application – no taping required.
- Lightweight, easy-to-handle rolls
- Tested to EN13501-1:2018 – Bfl-S1.
- High tear & puncture resistance
- Anti-slip
- Flame-retardant.
- 100% waterproof
- Easy to cut with a knife.
- Personalised logo and branding printing available (Minimum quantities applicable)
- Film is blue in colour.

#### Limitations:

- Although this product has a high-level of slip resistance it may become slippery when wet. Mop up any spills immediately or replace where necessary.
- This product is for application to hard surfaces, DO NOT use on carpets. Use Proguard Carpet Protection film.
- Adhesion will be reduced on dusty surfaces. Vacuuming or mopping prior to use is recommended.
- Proguard Hard Surface Protection Film should be removed after a maximum of 3 months.
- Always check Proguard Hard Surface Protection Film is stuck firmly to surfaces before commencing work.
- Do not use underfloor heating whilst product is in situ.
- We advise that you test on a small, inconspicuous area before full application.
- It is the users' responsibility to determine suitability for use. If in doubt, contact technical services for advice.

#### Application:

Ensure surfaces to which Proguard Hard Surface Film is to be applied are clean, dust free and dry. Remove outer packaging from roll. Place roll on the floor facing the direction it is to be applied and unwind approx. 600mm of material. Ensure the roll is stuck by smoothing it out. Pull the roll towards you ensuring it goes in a straight line. Smooth out with hands or feet as it unwinds. An effective way of laying Proguard Hard Surface Film is to push the roll along with a soft broom/brush using the brush to smooth out and remove air bubbles as it unwinds.